

ACOUSTIC SOLUTIONS DAB-ICS100

Please read the WARNINGS below and the instruction booklet thoroughly. If you are in any doubt, please consult dabonwheels before proceeding or arrange professional installation. (Please see <http://www.dabonwheels.co.uk/Installation.html>)

WARNINGS

DO NOT INSTALL IN A MANNER THAT WOULD INTERFERE WITH THE DRIVER'S VISION, WITH THE SAFE OPERATION OF THE VEHICLE CONTROLS OR WITH THE VEHICLE SAFETY FUNCTIONS E.G. SEATBELTS AND AIRBAGS.

Allow plenty of time for installation; it's bound to go wrong if attempted in a rush!

The cable terminals and fuseholders will not withstand rough treatment. Please handle with care.

The remote control pod is not 'Quick release'; its telephone-type connectors are not designed for repeated, frequent use.

The labels on the supplied ISO/DIN FM/AM aerial lead are confusing. Use to connect the black box main unit to your existing radio as appropriate, in conjunction with the supplied ISO/DIN converter if necessary.

The frequency chart on the hideaway box is also confusing. Please refer instead to the chart in the instruction manual.

The instructions refer to the standard aerial cable being 5 metres long; 1.5 metres is more accurate.

About 2% of vehicles (Some BMWs, Minis, etc.) use non-standard aerial connectors. Adaptors are available here: http://www.dabonwheels.co.uk/Fakra_aerial_adaptor_kit.asp

The standard aerial is UNSUITABLE for use on reflective coated, double glazed and/or heated screens.

Once the glassmount DAB aerial has been fully installed, the system can only be returned for refund if it proves faulty. It is possible, however, for you to test the aerial to your satisfaction in a stationary vehicle by temporarily fixing it in place with sticky tape.

Neither the aerial nor the remote control pod mount will fix securely unless:

The glass surface to which it is installed is flat or almost flat.

The glass is spotlessly clean and dry at time of installation.

The glass is a minimum of 20 degrees Centigrade at time of installation and for 5 minutes thereafter.

Excess aerial cable should not be coiled since this can degrade reception performance.

With a little ingenuity the windscreen mount can be modified to provide as a neat console mount in many cars.

Your warranty for this product is with dabonwheels.

Questions? Email service@dabonwheels.co.uk

Reception can be vastly improved by upgrading the standard aerial. Please see: http://www.dabonwheels.co.uk/DAB_car_aerials.html